



ELDON ENCLOSURE SYSTEMS

RANGE & DIMENSIONS 10





MAS, MAD

Multi-Mount Mild steel wall mounting enclosure, single door IP66 and double door IP55.



With mounting plate

Enclosure dimensions				Part No.
H	W	D		
200	200	155		MAS0202015R5
250	200	155		MAS0252015R5
	250	155		MAS0252515R5
300	250	155		MAS0302515R5
		210		MAS0302521R5
	300	155		MAS0303015R5
		210		MAS0303021R5
350	250	155		MAS0352515R5
400	300	155		MAS0403015R5
		210		MAS0403021R5
	400	210		MAS0404021R5
		500	210	MAS0405021R5
		600	210	MAS0406021R5
500	300	210		MAS0503021R5
	400	155		MAS0504015R5
		210		MAS0504021R5
		260		MAS0504026R5
		300		MAS0504030R5
	500	210		MAS0505021R5
		300		MAS0505030R5
600	400	155		MAS0604015R5
		210		MAS0604021R5
		260		MAS0604026R5
		300		MAS0604030R5
	500	155		MAS0605015R5
		210		MAS0605021R5
		260		MAS0605026R5
		300		MAS0605030R5
	600	210		MAS0606021R5
		300		MAS0606030R5
		400		MAS0606040R5
	800	300		MAS0608030R5
700	500	210		MAS0705021R5
		260		MAS0705026R5
800	400	300		MAS0804030R5
	600	210		MAS0806021R5
		260		MAS0806026R5
		300		MAS0806030R5
		400		MAS0806040R5
	800	210		MAS0808021R5
		300		MAS0808030R5
		400		MAS0808040R5
1000	600	260		MAS1006026R5
		300		MAS1006030R5
	800	260		MAS1008026R5
		300		MAS1008030R5
		400		MAS1008040R5
1200	600	300		MAS1206030R5
	800	300		MAS1208030R5
		400		MAS1208040R5
600	800	300		MAD0608030R5
800	1200	300		MAD0801230R5
1000	1000	300		MAD1001030R5
1200	1000	300		MAD1201030R5
	1200	300		MAD1201230R5
		400		MAD1201240R5
1400	1000	300		MAD1401030R5

Add "PE" to the existing part number if you do not require a mounting plate (e.g. MAS1206030PER5). For wall mounting brackets: order AW41.

MAP

Multi-Mount Mild steel wall mounting enclosure, panel. IP66



With mounting plate

Enclosure dimensions				Part No.
H	W	D		
300	600	300		MAP0306030R5
	800	300		MAP0308030R5
	1000	300		MAP0310030R5
	1200	300		MAP0312030R5

Add "PE" to the existing part number if you do not require a mounting plate (e.g. MAP0312030PER5). Gland plates and gaskets are not included.

MKS, MKD

Multi-Flex Mild steel floor standing Compact enclosure. Single door IP66, double door IP55.



With mounting plate

Enclosure dimensions				Part No.
H	W	D		
1600	600	400		MKS16064R5
	800	400		MKS16084R5
		500		MKS16085R5
	1000	400		MKS16104R5
		500		MKS16105R5
1800	600	400		MKS18064R5
	800	400		MKS18084R5
		500		MKS18085R5
	1000	400		MKS18104R5
2000	600	400		MKS20064R5
	800	400		MKS20084R5
		500		MKS20085R5
	1000	400		MKS20104R5
		500		MKS20105R5
1600	1200	400		MKD16124R5
1800	1200	400		MKD18124R5
	1600	400		MKD18164R5
		500		MKD18165R5
2000	1200	400		MKD20124R5
	1600	400		MKD20164R5
		500		MKD20165R5

Add "PE" to the existing part number if you do not require a mounting plate (e.g. MKD20165PER5)

MCS, MCD

Multi-Flex, Mild steel floor standing combination enclosure, single door IP56, double door IP55.



With mounting plate

Enclosure dimensions				Part No.
H	W	D		
1800	600	400		MCS18064R5
		500		MCS18065R5
		600		MCS18066R5
	800	400		MCS18084R5
		500		MCS18085R5
		600		MCS18086R5
	1000	400		MCS18104R5
		500		MCS18105R5
2000	400	400		*MCS20044R5
		500		*MCS20045R5
		600		*MCS20046R5
	800	400		*MCS20048R5
		500		MCS20064R5
		600		MCS20065R5
		800		MCS20066R5
	700	400		MCS20074R5
	800	400		MCS20084R5
		500		MCS20085R5
		600		MCS20086R5
	1000	400		MCS20104R5
		500		MCS20105R5
		600		MCS20106R5
		800		MCS20108R5
2200	600	600		MCS22066R5
		800		MCS22068R5
	800	600		MCS22086R5
		800		MCS22088R5
1800	800	500		MCD18085R5
	1000	400		MCD18104R5
		500		MCD18105R5
	1200	400		MCD18124R5
		500		MCD18125R5
	1600	400		MCD18164R5
2000	800	500		MCD20085R5
	1000	400		MCD20104R5
		500		MCD20105R5
		600		MCD20106R5
		800		MCD20108R5
	1200	400		MCD20124R5
		500		MCD20125R5
		600		MCD20126R5
		800		MCD20128R5
	1400	400		MCD20144R5
	1600	400		MCD20164R5
		500		MCD20165R5
		600		MCD20166R5
2200	1000	600		MCD22106R5
	1200	600		MCD22126R5

Add "PE" to the existing part number if you do not require a mounting plate (e.g. MCD22126PER5). Suitable for combining with other enclosures. Side panels available as an accessory.

* For enclosures with width 400 mm: mounting plate, door frame and bottom plates are excluded.

MCI

Multi-Flex, Mild steel floor standing industrial ICT enclosure, IP56, with 19"profiles



Height U	W	D	H	Part No.
22	600	600	1100	MCI11066R5
29	800	600	1400	MCI14086R5
33	600	600	1600	MCI16066R5
38	600	600	1800	MCI18066R5
		800	1800	MCI18068R5
	800	600	1800	MCI18086R5
42	600	600	2000	MCI20066R5
		800	2000	MCI20068R5
	800	600	2000	MCI20086R5
		800	2000	MCI20088R5
47	600	600	2200	MCI22066R5
		800	2200	MCI22068R5
	800	600	2200	MCI22086R5
		800	2200	MCI22088R5
		900	2200	MCI22089R5

Side panels and front plain or glazed doors are available as an accessory. Supplied without mounting plate

MCM

Multi-Flex, Mild steel floor standing industrial computer enclosure, with monitor shelf. IP55



Enclosure dimensions				Part No.
H	W	D		
1600	600	600		MCM16066R5
		800		MCM16068R5

Your corporate logo can be displayed on the top profile.

MPC, MPCS

Flexible console system in Mild steel and Stainless steel. Single door IP66 and double door IP55



Top section units				
Mild steel				
H	W	D	Part No.	
500	600	494	MPC061R5	
	800	494	MPC081R5	
	1000	494	MPC101R5	
	1200	494	MPC121R5	
	1600	494	MPC161R5	

Desk units				
Mild steel				
H	W	D	Part No.	
250	600	985	MPC062R5	
	800	985	MPC082R5	
	1000	985	MPC102R5	
	1200	985	MPC122R5	
	1600	985	MPC162R5	

Base units with mounting plate				
Mild steel				
H	W	D	Part No.	
700	600	500	MPC063R5	
	800	500	MPC083R5	
	1000	500	MPC103R5	
	1200	500	MPC123R5	
	1600	500	MPC163R5	

For ordering a Stainless steel console system: MPCS+the rest of the part number (e.g. MPCS061). R5 is for mild steel version only. To order a Stainless steel console in high grade 316, please add 316 to the catalogue number (e.g. MPCS063-316)

MPG, MPGS

Compact console system in Mild steel and Stainless steel. Single door IP66, double door IP55



Mild steel				
H	W	D	Part No.	
985	600	400	MPG06R5	
	800	400	MPG08R5	
	1000	400	MPG10R5	
	1200	400	MPG12R5	
	1600	400	MPG16R5	

For ordering a Stainless steel console system: MPGS+ the rest of the reference (e.g. MPGS16). R5 is for mild steel version only. To order a Stainless steel console in high grade 316, please add 316 to the catalogue number (e.g. MPGS16-316). Single door is IP66, double door is IP55. Note: Only 1200 and 1600 wide consoles have double doors.

ASR, ADR

Wall mounting enclosure in Stainless steel, single door IP66, double door IP55



Enclosure dimensions				Part No.
H	W	D		
180	240	150	ASR0182415	
240	240	150	ASR0242415	
	360	150	ASR0243615	
300	200	150	ASR0302015	
360	240	150	ASR0362415	
400	300	150	ASR0403015	
	400	210	ASR0404021	
	600	210	ASR0406021	
500	400	210	ASR0504021	
	500	210	ASR0505021	
600	400	210	ASR0604021	
	600	210	ASR0606021	
		300	ASR0606030	
	800	300	ASR0608030	
800	600	210	ASR0806021	
	300		ASR0806030	
	800	300	ASR0808030	
1000	800	300	ASR1008030	
1200	800	300	ASR1208030	
		400	ASR1208040	
1400	800	400	ASR1408040	
1000	1000	300	ADR1001030	
	1200	300	ADR1001230	
1200	1200	400	ADR1201240	

To order a Stainless steel enclosure in high grade 316, please add 316 to the catalogue number (e.g. ADR12124-316). For wall mounting brackets: order AWS41.

CSS, CDS

Floor standing enclosure in Stainless steel, single or double door, IP55



With mounting plate				Part No.
H	W	D		
1800	600	500	CSS18065	
	800	500	CSS18085	
	1000	500	CSS18105	
2000	600	600	CSS20066	
	800	600	CSS20086	
	1000	600	CSS20106	
1800	1000	500	CDS18105	
	1200	500	CDS18125	
2000	1200	600	CDS20126	

Add "PE" to the existing part number if you do not require a mounting plate (e.g. CDS20216PE). To order a Stainless steel enclosure in high grade 316, please add 316 to the catalogue number (e.g. CDS20126-316). Side panels, available as an accessory



AFS

Wall mounting enclosure with sloping roof in Stainless steel.

Single door, IP66



Single door with sloping roof
Meeting HACCP standards

Enclosure dimensions				Part No.
H	W	D		
300	200	155		AFS03021
400	300	155		AFS04031
	400	210		AFS04042
	600	210		AFS04062
500	500	210		AFS05052
600	400	210		AFS06042
	600	210		AFS06062
		300		AFS06063
	800	300		AFS06083
800	600	210		AFS08062
		300		AFS08063
	800	210		AFS08082
		300		AFS08083
1000	800	300		AFS10083
1200	600	300		AFS12063
	800	300		AFS12083
		400		AFS12084
1400	800	400		AFS14084

To order a Stainless steel enclosure in high grade 316, please add 316 to the catalogue number (e.g. AFS03021-316). For wall mounting brackets, order AWS41

KSS, KDS

Floor standing enclosure in Stainless steel, single door IP66, double door IP55



H	W	D	Part No.
1600	600	400	KSS16064
	800	400	KSS16084
	1000	400	KSS16104
1800	600	400	KSS18064
	800	400	KSS18084
	1000	400	KSS18104
2000	800	400	KSS20084
	1000	400	KSS20104
1600	1200	400	KDS16124
1800	1200	400	KDS18124
	1600	400	KDS18164
2000	1200	400	KDS20124
	1600	400	KDS20164

To order a Stainless steel enclosure in high grade 316, please add 316 to the catalogue number (e.g. KSS18064-316). Mounting plate excluded, add PE to the article number (e.g. KSS18064PE).

EF, EFA

For cooling the enclosure, Eldon can offer cooling units, heat exchangers or the following filter fans and exhaust filters:



Power (W)	Air flow (m³/h)	Cut out dim.	Part No.
12	16		EF100R5
19	44		EF200R5
	110		EF220R5
19	116		EF250R5
45	231		EF300R5
115	370		EF500R5
115	445		EF600R5
169	560		EF700R5
		92 x 92	EFA100R5
		125 x 125	EFA200R5
		177 x 177	EFA220R5
		223 x 223	EFA250-300R5
		291 x 291	EFA500-700R5

ETR

Thermostats for regulating heaters and filter fans

Setting range thermostat: 0°C to 60°C
Connection: 2 pole clamp 2,5 mm²



Description	Part No.
Normally opened contact	ETR201
Normally closed contact	ETR202
Normally opened	*ETR201ULF
Normally closed	*ETR202ULF

*UL approved

UCP, UCPT

Uniplast polyester wall mounting enclosure. Complies with IP66.



Plain door

H	W	D	Part No.
315	215	170	UCP320
415	315	170	UCP430
515	415	230	UCP540
615	415	230	UCP640
735	535	270	UCP750
835	635	300	UCP860
1035	835	300	UCP1080

UDP, UDPT

Uniplast polyester wall mounting enclosure, modular version. IP65 for plain doors, IP55 for transparent doors



Plain door

H	W	D	Doors	Part No.
500	500	320	1	*UDP5050
	750	320	1	*UDP5075
750	500	320	1	*UDP7550
	750	320	1	*UDP7575
	1000	320	1	*UDP75100
	500+750	320	2	UDP75125
1000	500	320	1	*UDP10050
	750	320	1	*UDP10075
	1000	320	1	UDP100100
	500+500	320	2	UDP100102
	500+750	320	2	UDP100125
1250	750	320	1	*UDP12575
500+750	1000	320	2	UDP125100
500+750	1000	320	2	UDP125102

* For transparent door: UDPT + rest of the art. nr. (e.g. UDPT1080). Different types of mounting plates are available as an accessory.

	500	750	1000	1250
500				
750				
1000				
1250				

STB

Terminal box in mild steel and Stainless steel. IP66



H	W	D	Part No.
150	150	80	STB151508
		120	STB151512
	300	80	STB153008
		120	STB153012
200	200	80	STB202008
		120	STB202012
	300	80	STB203008
		120	STB203012
	400	80	STB204008
		120	STB204012
	500	120	STB205012
	600	120	STB206012
	800	120	STB208012
300	300	80	STB303008
		120	STB303012
	400	120	STB304012
	500	120	STB305012
	600	120	STB306012
400	400	120	STB404012
	600	120	STB406012
	800	120	STB408012

For orders of Stainless steel terminal boxes: ILS + rest of the art.nr.

HALP

Aluminium box, IP65



H	W	D	Weight	Part No.
45	50	30	0.07	HALP050503GE
64	58	36	0.17	HALP060604GE
	98	36	0.22	HALP061004GE
	150	36	0.33	HALP061504GE
80	75	57	0.29	HALP080806GE
	125	57	0.44	HALP081306GE
	175	57	0.54	HALP081806GE
	250	57	0.71	HALP082506GE
122	122	80	0.86	HALP121208GE
		90	0.94	HALP121209GE
	220	80	1.29	HALP122208GE
		90	1.32	HALP122209GE
	360	80	1.41	HALP123608GE
160	160	90	1.96	HALP161609GE
	260	90	2.55	HALP162609GE
	360	90	4.31	HALP163609GE
	560	90	2.75	HALP165609GE
230	200	110	4.27	HALP232011GE
	330	110	5.75	HALP233311GE
		180	4.81	HALP233318GE
	400	110	6.89	HALP234011GE
	600	110	6.88	HALP236011GE

DABP

OEM ABS box. IP66/67



H	W	D	Weight	Part No.
53	55	36	0.04	DABP050504GE
	63	36	0.05	DABP050704GE
	80	56	0.12	DABP080806GE
		86	0.14	DABP080809GE
	120	56	0.15	DABP081206GE
		86	0.19	DABP081209GE
	160	56	0.19	DABP081606GE
		86	0.23	DABP081609GE
120	122	56	0.20	DABP121206GE
		86	0.26	DABP121209GE
	160	91	0.34	DABP121609GE
	200	86	0.38	DABP122009GE
150	200	76	0.39	DABP152008GE
160	240	91	0.55	DABP162409GE
		121	0.68	DABP162412GE
230	300	86	0.85	DABP233009GE
		111	0.90	DABP233011GE

ILS

Stainless steel terminal box. IP67/IP66



H	W	D	Part No.
150	150	80	ILS151508
		120	ILS151512
	300	80	ILS153008
		120	ILS153012
200	200	80	ILS202008
		120	ILS202012
	300	80	ILS203008
		120	ILS203012
	400	80	ILS204008
		120	ILS204012
	500	120	ILS205012
	600	120	ILS206012
	800	120	ILS208012
300	300	80	ILS303008
		120	ILS303012
	400	120	ILS304012
	500	120	ILS305012
	600	120	ILS306012
400	400	120	ILS404012
	600	120	ILS406012
	800	120	ILS408012

MGRP

Polyester box, IP65



H	W	D	Weight	Part No.
75	80	55	0.23	MGRP080806GE
		75	0.31	MGRP080808GE
	110	55	0.30	MGRP081106GE
		75	0.38	MGRP081108GE
	160	55	0.41	MGRP081606GE
		75	0.43	MGRP081608GE
	190	55	0.45	MGRP081906GE
		75	0.53	MGRP081908GE
120	122	90	0.75	MGRP121209GE
	220	90	1.06	MGRP122209GE
160	160	90	1.13	MGRP161609GE
	260	90	1.17	MGRP162609GE
	360	90	2.15	MGRP163609GE
	560	90	3.20	MGRP165609GE
250	255	120	2.66	MGRP252612GE
	400	120	3.65	MGRP254012GE
405	400	120	5.58	MGRP414012GE

SABP

Small ABS box. IP66/67



H	W	D	Weight	Part No.
75	125	75	184	SABP081308GE
		100	243	SABP081310GE
		125	266	SABP081313GE
125	125	75	250	SABP131308GE
		100	317	SABP131310GE
		125	353	SABP131313GE
	175	75	328	SABP131808GE
		100	401	SABP131810GE
		125	459	SABP131813GE
	150	75	521	SABP131815GE
175	175	75	392	SABP181808GE
		100	490	SABP181810GE
		125	557	SABP181813GE
		150	616	SABP181815GE
	250	75	553	SABP182508GE
		100	666	SABP182510GE
		150	842	SABP182515GE



OABP

Large ABS box. IP66/67



With grey cover

H	W	D	Weight	Part No.
200	200	132	894	OABP202013GE
300	132	1176	OABP203013GE	
400	132	1467	OABP204013GE	
300	300	132	1510	OABP303013GE
400	132	1950	OABP304013GE	
600	132	2696	OABP306013GE	
400	600	132	3484	OABP406013GE

With transparent cover

H	W	D	Weight	Part No.
200	200	132	926	OABP202013TE
300	132	1218	OABP203013TE	
400	132	1512	OABP204013TE	
300	300	132	1568	OABP303013TE
400	132	2003	OABP304013TE	
600	132	2765	OABP306013TE	
400	600	132	3567	OABP406013TE

OPCP

Large Polycarbonate box. IP66/67



With grey cover

H	W	D	Weight (g)	Part No.
200	200	130	1039	OPCP202013GE
300	130	1349	OPCP203013GE	
400	130	1674	OPCP204013GE	
300	300	130	1738	OPCP303013GE
400	130	2199	OPCP304013GE	
400	600	130	3964	OPCP406013GE
300	600	130	3000	OPCP306013GE

With transparent cover

H	W	D	Weight (g)	Part No.
200	200	130	1039	OPCP202013TE
300	130	1349	OPCP203013TE	
400	130	1674	OPCP204013TE	
300	300	130	1738	OPCP303013TE
400	130	2199	OPCP304013TE	
600	130	3000	OPCP306013TE	
400	600	130	3964	OPCP406013TE

SASL

Swing Arm SL



Description	Part No.
Rotation elbow SL	SAAE1SL
Base bracket turnable SL	SABT1SL
Base of wall flange SL	SABW1SL
Intermediate joint SL	SAIJ1SL
Reinforced elbow SL	SARE1SL
Set-up joint SL	SASJ1SL
Wall joint with horizontal outlet SL	SAWJH1SL
Wall joint with vertical outlet SL	SAWJV1SL
Coupling SL	SAC1SL
Elbow coupling SL	SAEC1SL
Elbow SL	SAE1SL
Operator Arm Section Profile	SAS025CSL
Operator Arm Section Profile	SAS025OS
Operator Arm Section Profile	SAS050CSL
Operator Arm Section Profile	SAS050OS
Operator Arm Section Profile	SAS100CSL
Operator Arm Section Profile	SAS100OS
Operator Arm Section Profile	SAS200CSL
Operator Arm Section Profile	SAS200OS

Additional Swing Arms with higher loading capacity are available on request.

DPCP

OEM Polycarbonate box. IP66/67



H	W	D	Weight	Part No.
53	55	36	0.05	DPCP050504GE
63	36	0.06	DPCP050704GE	
80	82	56	0.13	DPCP080806GE
		86	0.16	DPCP080809GE
120	56	0.17	DPCP081206GE	
		86	0.21	DPCP081209GE
160	56	0.19	DPCP081606GE	
		86	0.26	DPCP081609GE
120	122	56	0.22	DPCP121206GE
		86	0.29	DPCP121209GE
160	91	0.36	DPCP121609GE	
200	86	0.42	DPCP122009GE	
150	200	76	0.42	DPCP152008GE
160	240	91	0.61	DPCP162409GE
		121	0.74	DPCP162412GE
230	300	86	0.97	DPCP233009GE
		111	1.11	DPCP233011GE

OICP

Operator Interface Control Panel. IP65



Enclosure dimensions			
H	W	D	Part No.
309	525	200	OICP305220
345	395	200	OICP343920
354	525	200	OICP355220
398	525	200	OICP395220
415	470	200	OICP414720
495	542	200	OICP495420

The external Enclosure dimension is increased by 16.5mm on the side where there is a grip profile.

EBG

EIBox 19" ICT Wall mounting enclosure, IP10.



Flat Pack - Glazed Door

Height U	H	W	D	Part No.
6	350	570	400	EBG064
9	475	570	400	EBG094
12	600	570	400	EBG124
15	750	570	400	EBG154
18	875	570	400	EBG184
6	350	570	500	EBG065
9	475	570	500	EBG095
12	600	570	500	EBG125
15	750	570	500	EBG155
18	875	570	500	EBG185
21	1000	570	500	EBG215

Mounted - Glazed Door

Height U	H	W	D	Part No.
9	475	570	600	EBG096
12	600	570	600	EBG126
15	750	570	600	EBG156
18	875	570	600	EBG186

Mounted - Plain Steel Door

Height U	H	W	D	Part No.
9	475	570	600	EBS096
15	750	570	600	EBS156

EBP

Multi section enclosure with rear section and glazed door, IP10



Height U	H	W	D	Part No.
6	350	570	650	EBP066
9	475	570	650	EBP096
12	600	570	650	EBP126
15	750	570	650	EBP156
18	875	570	650	EBP186

BTN

Open Data Rack



Height U	W	H	h	Part No.
45	609	2092	2009,5	BTN45

EPR

EIRack, Floor Standing Patch Rack. IP30



Without side panels

Height U	W	D	H	Weight	Part No.
25	600	600	1200	58.5	EPRC12066
	800	800	1200	71.5	EPRC12088
39	600	600	1820	81.0	EPRC18066
	800	800	1820	95.0	EPRC18088
43	600	600	2000	86.5	EPRC20066
	800	800	2000	103.0	EPRC20088
48	600	600	2220	94.5	EPRC22066
	800	800	2220	112.0	EPRC22088

With side panels

Height U	W	D	H	Weight	Part No.
25	600	600	1200	75.5	EPR12066
	800	800	1200	94.5	EPR12088
39	600	600	1820	107.0	EPR18066
	800	800	1820	129.5	EPR18088
43	600	600	2000	115.0	EPR20066
	800	800	2000	141.5	EPR20088
48	600	600	2220	134.5	EPR22066
	800	800	2220	154.0	EPR22088

EPD

EIRack, Floor Standing Data Rack. IP30



Without side panels

Height U	W	D	H	Weight	Part No.
25	600	600	1200	56.5	EPDC12066
	800	800	1200	61.5	EPDC12088
43	600	600	2000	71.5	EPDC12088
	800	800	2000	88.0	EPDC20066
	100	2000	91.5	EPDC20068	
	800	800	2000	103.0	EPDC20088
	100	2000	107.0	EPDC200810	
48	600	600	2220	94.5	EPDC22066
	800	2220	96.0	EPDC22068	
	100	2220	120.0	EPDC220610	
	800	800	2220	112.0	EPDC22088
	100	2220	116.0	EPDC220810	

With side panels

Height U	W	D	H	Weight	Part No.
25	600	600	1200	77.0	EPD12066
	800	1200	84.5	EPD12068	
	800	800	1200	94.5	EPD12088
43	600	600	2000	115.0	EPD20066
	800	2000	126.0	EPD20068	
	1000	2000	139.5	EPD200610	
	800	800	2000	141.5	EPD20088
	1000	2000	155.0	EPD200810	
48	600	600	2220	134.5	EPD22066
	800	2220	138.0	EPD22068	
	1000	2220	173.0	EPD220610	
	800	800	2220	154.0	EPD22088
	1000	2220	169.0	EPD220810	

ESR, ESRB

EIRack, 19" Floor standing ICT Server rack, IP30.



Without side panels

Height U	W	D	H	Part No.
43	600	1000	2000	ESRC200610
	800	1000	2000	ESRC200810
48	600	1000	2200	ESRC220610
	800	1000	2200	ESRC220810

Standard in RAL7035

HPCM

1U, Master Remote Control unit with IP address



Length	Outlets	Part No.
19" (438,5mm)	8x C13	HPCM119108
Vertical	12x C19	HPCM100312
	24x13 +8x C19	HPCM100324

EDRM

Telescopic TFT-screen



U	Screen size	KVM switch	N° of ports	Part No.
1	17	no	1	EDRM17000
		no	1	EDRM17U000
		yes	4	EDRM17KU04
		yes	8	EDRM17KA08
			16	EDRM17KA16
		yes	8	EDRM17KC08
			16	EDRM17KC16
			32	EDRM17KC32



ELDON Export Department

Postbus 38 - Tussendiepen 64-66 - NL-9200 AA -The Netherlands

Tel: +31 512 580 123 - Fax: +31 512 517 117

eldon.export@eldon.com - www.eldon.com